

SAMSUNG
ELECTRONICS



Add an **SRP-275A Kitchen Printer** to your ER-390M



Add an **Ellix 20 Thermal Bill Printer** to your ER-390M



Add a **Voyager Bar Code Scanner** to your ER-390M



Add a **Modem** to your ER-390M for remote P.C. comms



Add **Samstock Stock Control Software** to your P.C.



PC Utility available for the ER-390M

**COMPATIBLE PERIPHERALS
AND STOCK CONTROL SOFTWARE.**

From the makers of Samsung™ Cash Registers

SAM4S

ER-390M

- **Low cost cash register!**
- **Drop & print thermal printer!**
- **No ink ribbons or rollers!**
- **2 line backlit operator display!**
- **Overlapping Cashier or Table Management!**

If you need a simple, quick, quiet and economical cash register then the ER-390M fits the bill.

If you want a low cost cash register that will grow with your business then the ER-390M is the cash register for you.

With 60 programmable PLU's on a splash proof flat keyboard the ER-390M is the ideal choice for any Hospitality or Retail environment



SAMSTOCK

Spares for ER-390M

Part No.	Item
57*57T	Thermal Till Roll
DRW037	Drawer Base
DRW038	Drawer Insert



Flat splashproof keyboard with 60 PLU's



2 Line Operator Display and 10 Digit VFD Customer Display



57mm Wide Thermal Receipt from Single Station Clam Shell Printer



The cash drawer has four notes and eight coin compartments



PC Utility available for the ER-390M

OPTIONAL PERIPHERALS & UTILITY/ SOFTWARE

- SRP-275 Dot Matrix Kitchen Printer
- Ellix 20 Thermal Printer
- High Speed Modem

- Programming Utility Software
- Samstock Stock Control Software
- Bar Code Scanner

**S P E C I F I C A T I O N E R - 3 9 0 M****DEPARTMENTS**

12

PLU's

300 Min - 8000 Max.

GROUPS

20

ELECTRONIC JOURNAL (DEFAULT)

3000 Lines

DESCRIPTORS

18 Character

CLERKS

15

BUFFER RECEIPT

Yes

TRAINING MODE

Yes

RECEIPT PRE-AMBLE/POST-AMBLE

6 Lines Each

KP OPERATION

Yes

TENDERING

Cash/Cheque/Charge 8

CURRENCY CONVERSION

4 including Euro

DECIMAL POINT

7 Digits

GRAPHIC LOGO PRINTING

Yes 8 Lines

PRINTER**Type**

Single Station Thermal Clam Shell

Speed

13.3 Lines Per Sec

Paper Width

57mm

KEYBOARD

Flat 90 Key Splashproof

DISPLAY

2 Line Alpha Numeric LCD

MEMORY**Operator**

10 Digit VFD

Customer

4mbit

ROM

1 Mbit (Default) 4 Mbit (Option)

RAM

60 Days

MEMORY PROTECTION BATTERY

2 X RS-232

INTERFACE/COMMUNICATION

230v/50hz

POWER REQUIREMENT

Reg (25w)

POWER CONSUMPTION

4 Note & 8 Coin Compartments

DRAWER

32°F ~ 104°F (0°C ~ 40°C)

ENVIRONMENT TEMPERATURE

30% ~ 80% Rh

CONDITION/HUMIDITY

400 X 450 X 266

DIMENSION

400 X 450 X 112

WEIGHT

13.0 Kg

TYPICAL MEMORY ALLOCATION WITH 1 RAM CHIP

- PLU 8000
- CLERKS 99
- GROUPS 99
- CHECKS 500
- LINES PER CHECK 100
- LEVELS 2 prices/5 modifiers
- MIX & MATCH 99

TYPICAL MEMORY ALLOCATION WITH NO RAM CHIP

- PLU 300
- CLERKS 10
- GROUPS 20
- CHECKS 15
- LINES PER CHECK 30
- LEVELS 1
- MIX & MATCH 10

Distributed by:

SAM4S